

TRANSMISSION RS FE 80W-90



GEAR OIL

USES

- Gear boxes, axles, transfer boxes.
- All types of gears when API MT-1, API GL-4 or API GL-5 is required.
- Specially recommended for highly loaded hypoid gears.

PROPERTIES

- High viscosity index.
- High Extreme-Pressure properties. Excellent antifoam, anticorrosive and antirust properties.
- Extended drain interval
- Fuel saving.

CHARACTERISTICS

TRANSMISSION RS FE	Units	Grade SAE 80W-90
Volumetric mass at 15°C	kg/m ³	886
Viscosity at 40°C	mm ² /s	115
Viscosity at 100°C	mm ² /s	14.1
Viscosity index	-	123
Pour point	°C	-33

The typical characteristics mentioned represent mean values.

SPECIFICATIONS

API MT-1
API GL-4
API GL-5
MAN 3343 type M (ex MAN 3343 type ML)
Meets the requirements for all RENAULT TRUCKS axles (extended drain interval)
ZF TE-ML 02B, 05A, 07A, 12E, 16B, 17B, 19B

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX

TRANSMISSION RS FE 80W-90
NOVEMBER 2006
N° MPR 11/06



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant.